

# Non-classical logics

## Lecture 5: Many-valued logics

Viorica Sofronie-Stokkermans

`sofronie@uni-koblenz.de`

# Until now

---

## Classical logic

- Propositional logic (Syntax, Semantics)
- First-order logic (Syntax, Semantics)

Proof methods (resolution, tableaux)

# From now on: Non-Classical logics

---

- Many-valued logic (finitely-valued; infinitely-valued)
  - Syntax, semantics, Automated proof methods (resolution, tableaux)
  - Reduction to classical logic
- Modal logics (also description logics, dynamic logic)
  - Syntax, semantics, Automated proof methods (resolution, tableaux)
  - Reduction to classical logic
- Temporal logic (Linear time; branching time)
  - Syntax, semantics, Model checking

# From now on: Non-Classical logics

---

- **Many-valued logic** (finitely-valued; infinitely-valued)
  - Syntax, semantics, Automated proof methods (resolution, tableaux)
  - Reduction to classical logic
- Modal logics (also description logics, dynamic logic)
  - Syntax, semantics, Automated proof methods (resolution, tableaux)
  - Reduction to classical logic
- Temporal logic (Linear time; branching time)
  - Syntax, semantics, Model checking

# Many-valued logic

---

- Introduction
- Many-valued logics
  - 3-valued logic
  - finitely-valued logic
  - fuzzy logic
- Automated theorem proving (resolution, tableaux)
- Reduction to classical logic

# History and Motivation

---

Many-valued logics were introduced to model undefined or vague information

# History and Motivation

---



## Jan Łukasiewicz

Began to create systems of many-valued logic in 1920, using a third value “possible” to deal with Aristotle’s paradox of the sea battle.

- Jan Łukasiewicz:

*“On 3-valued logic”* (Polish) *Ruch Filozoficzny*, Vol. 5, 1920.

Later, **Jan Łukasiewicz** and **Alfred Tarski** together formulated a logic on  $n$  truth values where  $n \geq 2$ .

- Jan Łukasiewicz:

*Philosophische Bemerkungen zu mehrwertigen Systemen des Aussagenkalküls*. *Comptes rendus des séances de la Société des Sciences et des Lettres de Varsovie, Classe III*, Vol .23, 1930.

- S. McCall:

*Polish Logic: 1920–1939*. Oxford University Press, 1967.

# History

---




## **Emile L. Post**

Introduced (in 1921) the formulation of additional truth degrees with  $n \geq 2$  where  $n$  is the number of truth values (starting mainly from algebraic considerations).

- Emil Post:

*Introduction to a general theory of elementary propositions. American J. of Math., Vol. 43, 1921.*



## **S. C. Kleene:**

Introduced a 3-valued logic in order to express the fact that some recursive functions might be undefined.



# Applications of many-valued logic

---

- independence proofs
- modeling undefined function and predicate values (program verification)
- semantic of natural languages
- theory of logic programming: declarative description of operational semantics of negation
- modeling of electronic circuits
- modeling vagueness and uncertainty
- shape analysis (program verification)

# Literature

---

- J. B. Rosser, A. R. Turquette: Many-valued Logics. North-Holland, 1952.
- N. Rescher: Many-valued Logic. McGraw-Hill, 1989.
- Alasdair Urquhart: Handbook of Philosophical Logic, vol. 3, 1986.
- Bolc und Borowik: Many-Valued Logics. Springer Verlag 1992,

# Literature

---

- Matthias Baaz, Christian G. Fermüller:  
Resolution-Based Theorem Proving for Many valued Logics.  
J. Symb. Comput. 19(4): 353-391 (1995)
- Reiner Hähnle:  
Automated Deduction in Multiple-valued Logics.  
Clarendon Press, Oxford, 1993.
- Grzegorz Malinowski:  
Many-Valued Logics.  
Oxford Logic Guides, Vol. 25, Clarendon Press, Oxford, 1993.
- Siegfried Gottwald  
A Treatise On Many-Valued Logics. Studies in Logic and Computation,  
Vol. 9, Research Studies Press, 2001.

# Literature

---

- Harald Ganzinger and Viorica Sofronie-Stokkermans  
Chaining techniques for automated theorem proving in many-valued logic. ISMVL 2000.
- Viorica Sofronie-Stokkermans and Carsten Ihlemann  
Automated reasoning in some local extensions of ordered structures  
Multiple-Valued Logic and Soft Computing 13(4-6): 397-414, 2007.

# A motivating example

---

$B$ : the sky is blue

$R$ : it rains

$U$ : I take my umbrella

$$(B \rightarrow \neg R) \wedge (R \rightarrow U) \wedge (B \rightarrow \neg U) \wedge R$$

# A motivating example

---

$B$ : the sky is blue

$R$ : it rains

$U$ : I take my umbrella

$$(B \rightarrow \neg R) \wedge (R \rightarrow U) \wedge (B \rightarrow \neg U) \wedge R$$

Description of a situation: (partial) variable assignment  $v : \Pi \rightarrow \{0, 1\}$

$A$	$v(A)$
$B$	1
$R$	
$U$	0

# Truth tables in partial logic

---

$v$  partial valuation.

$v \sqsubseteq v_1$ :  $v_1$  is a total variable assignment which extends  $v$ .

## Example

Description of a situation:

(partial)  $v : \Pi \rightarrow \{0, 1\}$

<u>A</u>	<u><math>v(A)</math></u>	<u>A</u>	<u><math>v_1(A)</math></u>	<u><math>v_2(A)</math></u>
B	1	B	1	1
R		R	0	1
U	0	U	0	0

$v \sqsubseteq v_1, v \sqsubseteq v_2$

$v(F_1 \wedge F_2) = 0$  iff for all  $v_1$  with  $v \sqsubseteq v_1$  we have  $v_1(F_1 \wedge F_2) = 0$

$v(F_1 \wedge F_2) = 1$  iff for all  $v_1$  with  $v \sqsubseteq v_1$  we have  $v_1(F_1 \wedge F_2) = 1$

# Truth tables for partial logic

---

$\wedge$	1	undef	0
1	1	undef	0
undef	undef	undef	0
0	0	0	0

$\vee$	1	undef	0
1	1	1	1
undef	1	undef	undef
0	1	undef	0

$F$	$\neg F$
1	0
undef	undef
0	1



# A motivating example

---

$\wedge$	1	undef	0
1	1	undef	0
undef	undef	undef	0
0	0	0	0

$\vee$	1	undef	0
1	1	1	1
undef	1	undef	undef
0	1	undef	0

$F$	$\neg F$
1	0
undef	undef
0	1

$$(B \rightarrow \neg R) \wedge (R \rightarrow U) \wedge (B \rightarrow \neg U) \wedge R$$

Description of a situation: (partial) variable assignment  $v : \Pi \rightarrow \{0, 1\}$

$A$	$v(A)$	$F$	$v(F)$
B	1	$\neg B \vee \neg R$	undef
R	undef	$\neg R \vee U$	undef
U	0	$\neg B \vee \neg U$	1

# Another example

---

## Belnap's 4-valued logic

This particularly interesting system of MVL was the result of research on relevance logic, but it also has significance for computer science applications. Its truth degree set may be taken as

$$M = \{\{\}, \{0\}, \{1\}, \{0, 1\}\},$$

and the truth degrees interpreted as indicating (e.g. with respect to a database query for some particular state of affairs) that there is


- no information concerning this state of affairs,
- information saying that the state of affairs is false,
- information saying that the state of affairs is true,
- conflicting information saying that the state of affairs is true as well as false.

# Another example

---

**Belnap's 4-valued logic**  $M = \{\{\}, \{0\}, \{1\}, \{0, 1\}\}$

This set of truth degrees has two natural orderings:



$\wedge, \vee$ : sup/inf in the truth ordering

$\sim \{\} = \{\}, \quad \sim \{0, 1\} = \{0, 1\}, \quad \sim \{0\} = \{1\}, \quad \sim \{1\} = \{0\}$

**“Designated” values:** (What we can assume to be true)

Computer science:  $D = \{\{1\}\}$

Other applications (e.g. information bases):  $D = \{\{1\}, \{0, 1\}\}$

# Many-valued logics

---

- Syntax
- Semantics
- Applications
- Proof theory / Methods for automated reasoning

# 1 Syntax

---

- propositional variables
- logical operations

# Propositional Variables

---

Let  $\Pi$  be a set of **propositional variables**.

We use letters  $P, Q, R, S$ , to denote propositional variables.

# Logical operators

---

Let  $\mathcal{F}$  be a set of **logical operators**.

These logical operators could be the usual ones from classical logic

$$\{\neg/1, \vee/2, \wedge/2, \rightarrow/2, \leftrightarrow/2\}$$

but could also be other operations, with arbitrary arity.

# Propositional Formulas

---

$F_{\Pi}^{\mathcal{F}}$  is the set of propositional formulas over  $\Pi$  defined as follows:

$$\begin{array}{l} F, G, H \quad ::= \quad c \quad \quad \quad (c \text{ constant logical operator}) \\ \quad \quad \quad | \quad P, \quad P \in \Pi \quad \quad \quad (\text{atomic formula}) \\ \quad \quad \quad | \quad f(F_1, \dots, F_n) \quad \quad \quad (f \in \mathcal{F} \text{ with arity } n) \end{array}$$



# Example: Classical propositional logic

---

If  $\mathcal{F} = \{\top/0, \perp/0, \neg/1, \vee/2, \wedge/2, \rightarrow/2, \leftrightarrow/2\}$  then

$F_{\Pi}$  is the set of propositional formulas over  $\Pi$  is defined as follows:

$F, G, H$	$::=$	$\perp$	(falsum)
		$\top$	(verum)
		$P, P \in \Pi$	(atomic formula)
		$\neg F$	(negation)
		$(F \wedge G)$	(conjunction)
		$(F \vee G)$	(disjunction)
		$(F \rightarrow G)$	(implication)
		$(F \leftrightarrow G)$	(equivalence)

# Semantics

---

We assume that a set  $M = \{w_1, w_2, \dots, w_m\}$  of truth values is given.

We assume that a subset  $D \subseteq M$  of **designated** truth values is given.

## 1. Meaning of the logical operators

$$f \in \mathcal{F} \text{ with arity } n \quad \mapsto \quad f_M : M^n \rightarrow M$$

(truth tables for the operations in  $\mathcal{F}$ )

**Example 1:** If  $\mathcal{F}$  consists of the Boolean operations and  $M = B_2 = \{0, 1\}$  then specifying the meaning of the logical operations means giving the truth tables for the operations in  $\mathcal{F}$

$\neg_b$	
0	1
1	0

$\vee_b$	0	1
0	0	1
1	1	1

$\wedge_b$	0	1
0	0	0
1	0	1

# Semantics

---

We assume that a set  $M = \{w_1, \dots, w_m\}$  of truth values is given.

We assume that a subset  $D \subseteq M$  of **designated** truth values is given.

## 1. Meaning of the logical operators

$$f \in \mathcal{F} \text{ with arity } n \quad \mapsto \quad f_M : M^n \rightarrow M$$

(truth tables for the operations in  $\mathcal{F}$ )

**Example 2:** If  $\mathcal{F}$  consists of the operations  $\{\vee, \wedge, \neg\}$  and  $M = \{0, \text{undef}, 1\}$  then specifying the meaning of the logical operations means giving the truth tables for these operations e.g.

F	$\neg_u F$
1	0
undef	undef
0	1

$\wedge_u$	1	undef	0
1	1	undef	0
undef	undef	undef	0
0	0	0	0

$\vee_u$	1	undef	0
1	1	1	1
undef	1	undef	undef
0	1	undef	0

# Semantics

---

We assume that a set  $M = \{w_1, \dots, w_m\}$  of truth values is given.

We assume that a subset  $D \subseteq M$  of **designated** truth values is given.

## 1. Meaning of the logical operators

$$f \in \mathcal{F} \text{ with arity } n \quad \mapsto \quad f_M : M^n \rightarrow M$$

(truth tables for the operations in  $\mathcal{F}$ )

**Example 2:**  $\mathcal{F} = \{\vee, \wedge, \neg\}$  and  $M = \{\{\}, \{0\}, \{1\}, \{0, 1\}\}$ . The truth tables for these operations e.g.

F	F
{ }	{ }
{ 0 }	{ 1 }
{ 1 }	{ 0 }
{ 0, 1 }	{ 0, 1 }

$\wedge_B$	{ }	{ 0 }	{ 1 }	{ 0, 1 }
{ }	{ }	{ 0 }	{ }	{ 0 }
{ 0 }	{ 0 }	{ 0 }	{ 0 }	{ 0 }
{ 1 }	{ }	{ 0 }	{ 1 }	{ 0, 1 }
{ 0, 1 }	{ 0 }	{ 0 }	{ 0, 1 }	{ 0, 1 }

$\vee_B$	{ }	{ 0 }	{ 1 }	{ 0, 1 }
{ }	{ }	{ }	{ 1 }	{ 1 }
{ 0 }	{ }	{ 0 }	{ 1 }	{ 0, 1 }
{ 1 }	{ 1 }	{ 0, 1 }	{ 1 }	{ 0, 1 }
{ 0, 1 }	{ 1 }	{ 0, 1 }	{ 0, 1 }	{ 1 }

# Semantics

---

We assume that a set  $M = \{w_1, \dots, w_m\}$  of truth values is given.

We assume that a subset  $D \subseteq M$  of **designated** truth values is given.

## 2. The meaning of the propositional variables

A  $\Pi$ -valuation is a map

$$\mathcal{A} : \Pi \rightarrow M.$$

# Semantics

---

We assume that a set  $M = \{w_1, \dots, w_m\}$  of truth values is given.

We assume that a subset  $D \subseteq M$  of **designated** truth values is given.

## 3. Truth value of a formula in a valuation

Given an interpretation of the operation symbols  $(M, \{f_M\}_{f \in \mathcal{F}})$  and  $\Pi$ -valuation  $\mathcal{A} : \Pi \rightarrow M$ , the function  $\mathcal{A}^* : \Sigma\text{-formulas} \rightarrow M$  is defined inductively over the structure of  $F$  as follows:

$$\mathcal{A}^*(c) = c_M \text{ (for every constant operator } c \in \mathcal{F}\text{)}$$

$$\mathcal{A}^*(P) = \mathcal{A}(P)$$

$$\mathcal{A}^*(f(F_1, \dots, F_n)) = f_M(\mathcal{A}^*(F_1), \dots, \mathcal{A}^*(F_n))$$

For simplicity, we write  $\mathcal{A}$  instead of  $\mathcal{A}^*$ .

# Example 1: Classical logic

---

Given a  $\Pi$ -valuation  $\mathcal{A} : \Pi \rightarrow B_2 = \{0, 1\}$ , the function  $\mathcal{A}^* : \Sigma\text{-formulas} \rightarrow \{0, 1\}$  is defined inductively over the structure of  $F$  as follows:

$$\mathcal{A}^*(\perp) = 0$$

$$\mathcal{A}^*(\top) = 1$$

$$\mathcal{A}^*(P) = \mathcal{A}(P)$$

$$\mathcal{A}^*(\neg F) = \neg_b \mathcal{A}^*(F)$$

$$\mathcal{A}^*(F \circ G) = \circ_b(\mathcal{A}^*(F), \mathcal{A}^*(G))$$

with  $\circ_B$  the Boolean function associated with  $\circ \in \{\vee, \wedge, \rightarrow, \leftrightarrow\}$

## Example 2: Logic of undefinedness

---

Given a  $\Pi$ -valuation  $\mathcal{A} : \Pi \rightarrow M = \{0, \text{undef}, 1\}$ , the function  $\mathcal{A}^* : \Sigma\text{-formulas} \rightarrow \{0, \text{undef}, 1\}$  is defined inductively over the structure of  $F$  as follows:

$$\mathcal{A}^*(\perp) = 0$$

$$\mathcal{A}^*(\top) = 1$$

$$\mathcal{A}^*(P) = \mathcal{A}(P)$$

$$\mathcal{A}^*(\neg F) = \neg_u(\mathcal{A}^*(F))$$

$$\mathcal{A}^*(F \vee G) = \mathcal{A}^*(F) \vee_u \mathcal{A}^*(G)$$

$$\mathcal{A}^*(F \wedge G) = \mathcal{A}^*(F) \wedge_u \mathcal{A}^*(G)$$



## Example 3: Belnap's 4-valued logic

---

Given a  $\Pi$ -valuation  $\mathcal{A} : \Pi \rightarrow M = \{\{\}, \{0\}, \{1\}, \{0, 1\}\}$ , the function  $\mathcal{A}^* : \Sigma\text{-formulas} \rightarrow \{\{\}, \{0\}, \{1\}, \{0, 1\}\}$  is defined inductively over the structure of  $F$  as follows:

$$\mathcal{A}^*(\perp) = \{0\}$$

$$\mathcal{A}^*(\top) = \{1\}$$

$$\mathcal{A}^*(P) = \mathcal{A}(P)$$

$$\mathcal{A}^*(\neg F) = {}_B(\mathcal{A}^*(F))$$

$$\mathcal{A}^*(F \vee G) = \mathcal{A}^*(F) \vee_B \mathcal{A}^*(G)$$

$$\mathcal{A}^*(F \wedge G) = \mathcal{A}^*(F) \wedge_B \mathcal{A}^*(G)$$

# Models, Validity, and Satisfiability

---

$M = \{w_1, \dots, w_m\}$  set of truth values

$D \subseteq M$  set of **designated** truth values

$\mathcal{A} : \Pi \rightarrow M$ .

$F$  is **valid** in  $\mathcal{A}$  ( $\mathcal{A}$  is a **model** of  $F$ ;  $F$  holds under  $\mathcal{A}$ ):

$$\mathcal{A} \models F :\Leftrightarrow \mathcal{A}(F) \in D$$

$F$  is **valid** (or is a **tautology**):

$$\models F :\Leftrightarrow \mathcal{A} \models F \text{ for all } \Pi\text{-valuations } \mathcal{A}$$

$F$  is called **satisfiable** iff there exists an  $\mathcal{A}$  such that  $\mathcal{A} \models F$ .

Otherwise  $F$  is called **unsatisfiable** (or **contradictory**).

## The logic $\mathcal{L}_3$

---

Set of truth values:  $M = \{1, u, 0\}$ .

Designated truth values:  $D = \{1\}$ .

Logical operators:  $\mathcal{F} = \{\vee, \wedge, \neg, \sim\}$ .

# Truth tables for the operators

---

$\vee$	0	$u$	1
0	0	$u$	1
$u$	$u$	$u$	1
1	1	1	1

$\wedge$	0	$u$	1
0	0	0	0
$u$	0	$u$	$u$
1	0	$u$	1

$$v(F \wedge G) = \min(v(F), v(G))$$

$$v(F \vee G) = \max(v(F), v(G))$$

Under the assumption that  $0 < u < 1$ .

# Truth tables for negations

---

$A$	$\neg A$	$\sim A$	$\sim \neg A$	$\sim\sim A$	$\neg\neg A$	$\neg \sim A$
1	0	0	1	1	1	1
$u$	$u$	1	1	0	$u$	0
0	1	1	0	0	0	0

Translation in natural language:

$v(A) = 1$  gdw.  $A$  is true

$v(\neg A) = 1$  gdw.  $A$  is false

$v(\sim A) = 1$  gdw.  $A$  is not true

$v(\sim \neg A) = 1$  gdw.  $A$  is not false

# First-order many-valued logic

---

$M = \{w_1, \dots, w_m\}$  set of truth values

$D \subseteq M$  set of designated truth values.

## 1. Syntax

- non-logical symbols (domain-specific)  
⇒ terms, atomic formulas
- logical symbols  $\mathcal{F}$ , quantifiers  
⇒ formulae

# Signature

---

A signature

$$\Sigma = (\Omega, \Pi),$$

fixes an alphabet of non-logical symbols, where

- $\Omega$  is a set of **function symbols**  $f$  with **arity**  $n \geq 0$ , written  $f/n$ ,
- $\Pi$  is a set of **predicate symbols**  $p$  with **arity**  $m \geq 0$ , written  $p/m$ .

If  $n = 0$  then  $f$  is also called a **constant (symbol)**.

If  $m = 0$  then  $p$  is also called a **propositional variable**.

We use letters  $P, Q, R, S$ , to denote propositional variables.

# Variables, Terms

---

As in classical logic



# Atoms

---

**Atoms** (also called atomic formulas) over  $\Sigma$  are formed according to this syntax:

$$A, B ::= p(s_1, \dots, s_m) \quad , p/m \in \Pi$$
$$\left[ \quad \mid (s \approx t) \quad \text{(equation)} \quad \right]$$

In what follows we will only consider variants of first-order logic **without equality**.

# Logical Operations

---

$\mathcal{F}$  set of logical operations

$\mathcal{Q} = \{Q_1, \dots, Q_k\}$  set of quantifiers

# First-Order Formulas

---

$F_\Sigma(X)$  is the set of first-order formulas over  $\Sigma$  defined as follows:

$$\begin{array}{l} F, G, H \quad ::= \quad c \qquad \qquad \qquad (c \in \mathcal{F}, \text{ constant}) \\ \quad \quad \quad | \quad A \qquad \qquad \qquad \quad (\text{atomic formula}) \\ \quad \quad \quad | \quad f(F_1, \dots, F_n) \quad (f \in \mathcal{F} \text{ with arity } n) \\ \quad \quad \quad | \quad Qx F \qquad \qquad \quad (Q \in \mathcal{Q} \text{ is a quantifier}) \end{array}$$

# Bound and Free Variables

---

In  $QxF$ ,  $Q \in \mathcal{Q}$ , we call  $F$  the **scope** of the quantifier  $Qx$ .

An *occurrence* of a variable  $x$  is called **bound**, if it is inside the scope of a quantifier  $Qx$ .

Any other occurrence of a variable is called **free**.

Formulas without free variables are also called **closed formulas** or **sentential forms**.

Formulas without variables are called **ground**.

# Semantics

---

$M = \{1, \dots, m\}$  set of truth values

$D \subseteq M$  set of designated truth values.

Truth tables for the logical operations:

$$\{f_M : M^n \rightarrow M \mid f/n \in \mathcal{F}\}$$

“Truth tables” for the quantifiers:

$$\{Q_M : \mathcal{P}(M) \rightarrow M \mid Q \in \mathcal{Q}\}$$

**Examples:** If  $M = B_2 = \{0, 1\}$  then

$$\forall_{B_2} : \mathcal{P}(\{0, 1\}) \rightarrow \{0, 1\} \quad \forall_{B_2}(X) = \min(X)$$

$$\exists_{B_2} : \mathcal{P}(\{0, 1\}) \rightarrow \{0, 1\} \quad \exists_{B_2}(X) = \max(X)$$

# Structures

---

An  $M$ -valued  $\Sigma$ -algebra ( $\Sigma$ -interpretation or  $\Sigma$ -structure) is a triple

$$\mathcal{A} = (U, (f_{\mathcal{A}} : U^n \rightarrow U)_{f/n \in \Omega}, (p_{\mathcal{A}} : U^m \rightarrow M)_{p/m \in \Pi})$$

where  $U \neq \emptyset$  is a set, called the **universe** of  $\mathcal{A}$ .

Normally, by abuse of notation, we will have  $\mathcal{A}$  denote both the algebra and its universe.

By  $\Sigma\text{-Alg}^M$  we denote the class of all  $M$ -valued  $\Sigma$ -algebras.

# Assignments

---

Variable assignments  $\beta : X \rightarrow \mathcal{A}$

and extensions to terms  $\mathcal{A}(\beta) : T_\Sigma \rightarrow \mathcal{A}$  as in classical logic.

# Truth Value of a Formula in $\mathcal{A}$ with Respect to $\beta$

$\mathcal{A}(\beta) : F_{\Sigma}(X) \rightarrow M$  is defined inductively as follows:

$$\mathcal{A}(\beta)(c) = c_M$$

$$\mathcal{A}(\beta)(p(s_1, \dots, s_n)) = p_{\mathcal{A}}(\mathcal{A}(\beta)(s_1), \dots, \mathcal{A}(\beta)(s_n)) \in M$$

$$\mathcal{A}(\beta)(f(F_1, \dots, F_n)) = f_M(\mathcal{A}(\beta)(F_1), \dots, \mathcal{A}(\beta)(F_n))$$

$$\mathcal{A}(\beta)(QxF) = Q_M(\{\mathcal{A}(\beta[x \mapsto a])(F) \mid a \in U\})$$



# First-order version of $\mathcal{L}_3$

---

$$M = \{0, u, 1\}$$

$$D = \{1\}$$

$$\mathcal{F} = \{\vee, \wedge, \neg, \sim\}$$

truth values as the propositional version

$$\mathcal{Q} = \{\forall, \exists\}$$

$$\forall_M(S) = \begin{cases} 1 & \text{if } S = \{1\} \\ 0 & \text{if } 0 \in S \\ u & \text{otherwise} \end{cases} \quad \exists_M(S) = \begin{cases} 1 & \text{if } 1 \in S \\ 0 & \text{if } S = \{0\} \\ u & \text{otherwise} \end{cases}$$

# Interpretation of quantifiers

---

$\mathcal{A}(\beta)(\forall x F(x)) = 1$  iff for all  $a \in U_{\mathcal{A}}$ ,  $\mathcal{A}(\beta[x \mapsto a])(F(x)) = 1$

$\mathcal{A}(\beta)(\forall x F(x)) = 0$  iff for some  $a \in U_{\mathcal{A}}$ ,  $\mathcal{A}(\beta[x \mapsto a])(F(x)) = 0$

$\mathcal{A}(\beta)(\forall x F(x)) = u$  otherwise

$\mathcal{A}(\beta)(\exists x F(x)) = 1$  iff for some  $a \in U_{\mathcal{A}}$ ,  $\mathcal{A}(\beta[x \mapsto a])(F(x)) = 1$

$\mathcal{A}(\beta)(\exists x F(x)) = 0$  iff for all  $a \in U_{\mathcal{A}}$ ,  $\mathcal{A}(\beta[x \mapsto a])(F(x)) = 0$

$\mathcal{A}(\beta)(\exists x F(x)) = u$  otherwise

# Models, Validity, and Satisfiability

---

$F$  is **valid** in  $\mathcal{A}$  under assignment  $\beta$ :

$$\mathcal{A}, \beta \models F \quad :\Leftrightarrow \quad \mathcal{A}(\beta)(F) \in D$$

$F$  is **valid** in  $\mathcal{A}$  ( $\mathcal{A}$  is a **model** of  $F$ ):

$$\mathcal{A} \models F \quad :\Leftrightarrow \quad \mathcal{A}, \beta \models F, \text{ for all } \beta \in X \rightarrow U_{\mathcal{A}}$$

$F$  is **valid**:

$$\models F \quad :\Leftrightarrow \quad \mathcal{A} \models F, \text{ for all } \mathcal{A} \in \Sigma\text{-alg}$$

$F$  is called **satisfiable** iff there exist  $\mathcal{A}$  and  $\beta$  such that  $\mathcal{A}, \beta \models F$ .

Otherwise  $F$  is called **unsatisfiable**.

# Entailment

---

$N \models F :\Leftrightarrow$  for all  $\mathcal{A} \in \Sigma\text{-alg}$  and  $\beta \in X \rightarrow U_{\mathcal{A}}$ :  
if  $\mathcal{A}(\beta)(G) \in D$ , for all  $G \in N$ , then  $\mathcal{A}(\beta)(F) \in D$ .

# Models, Validity, and Satisfiability in $\mathcal{L}_3$

---

$F$  is **valid** in  $\mathcal{A}$  under assignment  $\beta$ :

$$\mathcal{A}, \beta \models_3 F \quad :\Leftrightarrow \quad \mathcal{A}(\beta)(F) = 1$$

$F$  is **valid** in  $\mathcal{A}$  ( $\mathcal{A}$  is a **model** of  $F$ ):

$$\mathcal{A} \models_3 F \quad :\Leftrightarrow \quad \mathcal{A}, \beta \models_3 F, \text{ for all } \beta \in X \rightarrow U_{\mathcal{A}}$$

$F$  is **valid** (or is a **tautology**):

$$\models_3 F \quad :\Leftrightarrow \quad \mathcal{A} \models_3 F, \text{ for all } \mathcal{A} \in \Sigma\text{-alg}$$

$F$  is called **satisfiable** iff there exist  $\mathcal{A}$  and  $\beta$  such that  $\mathcal{A}, \beta \models_3 F$ .

Otherwise  $F$  is called **unsatisfiable**.

## Entailment in $\mathcal{L}_3$

---

$N \models_3 F :\Leftrightarrow$  for all  $\mathcal{A} \in \Sigma\text{-alg}$  and  $\beta \in X \rightarrow U_{\mathcal{A}}$ :  
if  $\mathcal{A}(\beta)(G) = 1$ , for all  $G \in N$ , then  $\mathcal{A}(\beta)(F) = 1$ .

# Observations

---

- Every  $\mathcal{L}_3$ -tautology is also a two-valued tautology.
- Not every two-valued tautology is an  $\mathcal{L}_3$ -tautology.

Example:  $F \vee \neg F$ .